

Board's Reference:

MARKET WEIGHTON DRAINAGE BOARD
APPLICATION FOR OUTFALLS

Applicant:

Address :

.....

1. Watercourse:

2. National Grid Reference:

3. OS Number(s) of land to be drained:

4. Position and number of outfalls:

5. (a) Are tributary drains available into which the outfall(s) could be made ? **Yes/No**

(b) If 'Yes' why, cannot the outfall(s) be made into the tributary drain ? **give reason:-**

.....

6. **Type of headwall proposed:** - Prefabricated concrete slabs / Traditional Brick / In situ concrete.
(delete as appropriate) Proprietary outfall units / Blockwork / **Other** (please give details)

.....

SPECIFICATION - GENERAL

1. Outfalls must be completely recessed into the bank so as not to obstruct the free flow of water and such that maintenance machinery can work over them without risk of damage to either the outfalls or the machinery.

2. Each outfall shall include a concrete invert slab, brick or concrete headwall or other recognised purpose manufactured device erected in the manner suitable to prevent scour of the banks or bed of the watercourse, generally in accordance with the Boards standard details.

I apply for the Board's consent to carry out works described above.

I accept full responsibility for the design and construction of the works and I fully understand that the Board will be under no liability for any loss or damage which may arise out of their design, construction, maintenance or replacement.

Signed: **Address:**

Date:

Tel No:

This application should be returned to: -

The Clerk:- Market Weighton Drainage Board.
Burnby Hall,
Pocklington,
York, Y042 2QF.